

weber.prim FP-A

Ready to use, single component floor primer

Technical Data Sheet

Issued On: 10.02.2020

Revision No: 002

■ Description

Styrene/acrylate based, alkali resistant, colourless, ready to use, single component floor primer to be used on absorbent substrates prior to the application of cement based flooring screeds.

■ Advantages

- Provides high adherence
- Rapid setting
- High alkali resistance
- Easy to apply

■ Application areas

Applied on highly absorbent floors, floor levelling screeds and other cement based floorings to;

- Enhance adherence
- Speed up spreading
- Prevent cracks due to rapid water loss of the application substrate
- Prevent air bubbles



■ Application substrates

- Interior floors;
- Cement based screeds,
 - Levelling screeds,
 - Concrete,

Please consult us for all other application substrates.

■ Limits of application

- Not applicable on damp and wet substrates.
- Not applicable on weak and loose substrates.

■ Preparation of substrates

- The substrate should be clean, dry, smooth and sound.
- All gypsum, paint, glue, oil and cement residues should be removed from the substrate.
- The substrate should be free from dust.

■ Application conditions

- Ambient temperature between +5°C and +30°C.
- Substrate temperature should not be below +5°C.
- Avoid application in extremely hot and/or damp weather, strong wind or direct sunlight.

■ Application

- **weber.prim FP-A** is a ready-to-use primer. Mix the product before use without diluting and apply as a single coat using roller.
- Priming should be made homogeneously to the whole surface.
- White colour of the primer gets transparent while setting.
- Application of levelling screed should start at least 1 hour after the application of **weber.prim FP-A** depending on the structure of the substrate, ambient and surface temperature.
- All tools used for the application should be cleaned with clean water right after the application before drying.

■ Application tools

Roller, brush

■ Consumption

Approximately 0.14-0.18 l/m² (depending on the application substrate)

■ Storage

Packaging	5 and 20 liters plastic drum
Colour	White
Shelf life	<ul style="list-style-type: none">• 1 year from date of manufacture when stored unopened and undamaged in a dry, moisture-free environment, between +5°C and +25°C.• Packages should be protected against frost.

■ Safety precautions

- Use appropriate safety equipment (mask, gloves, glasses).
- Protect your eyes/face.
- Avoid direct contact with eyes and skin.
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical attention.
- Please read Safety Data Sheet (SDS) for further safety information.

LEGAL DISCLAIMER

Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş. is not responsible for any errors arising from the use of product beyond its intended purpose or not complying the application procedures mentioned above.

The stated times apply for 20°C substrate and ambient temperature; increase at lower temperatures and decrease at higher temperatures.

Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose of failure to comply with the forgoing application conditions and advice on the product.



Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye
Tel: +90 (232) 397 07 00 • www.t.weber • info@weber.com.tr • Çözüm Hattı 444 6 990

