

# weberprim C 70

## Façade primer

### Technical DataSheet

Release date: 3/28/2022

Revision date: 8/1/2022

#### ■ Product Description

Acrylic emulsion-based, façade primer with fillings.

#### ■ Area of Use

Applied as a primer on substrates especially with high absorptivity of which are high in exterior walls of buildings for the purpose of increasing adherence and reducing consumption of final layer such as coatings and paints

#### ■ Substrates

Exterior walls;  
- Cement based renders,  
- Concrete (**webertec R**, **webertec RK** or **webertec RM** applied),  
- Gas concrete (gas concrete render applied),  
Applied before **webertex multicolor** and **webertex p-color** application.

• Please consult us for all other application substrates.

#### ■ Application Conditions

- Ambient temperature is between +5 °C and +30 °C. • Avoid application in very damp and/or hot weather. • It should not be used on substrates which are frozen or melting or have the risk of frost or rain within 24 hours.

#### ■ Application

- **weberprim C 70** is diluted in the ratio of 10/1 (**weberprim C 100**/water) and mixed until it reaches a homogenous state and is applied as single layer with lambskin roller or brush.
- Paint or coating application should be started at least 12 hours after the application of **weberprim C 70**.  
Note : Diluted **weberprim C 70** should be mixed and kept in homogenous state and it should not deposit.
- Drying time is minimum 12 hours.

#### ■ Tools

Lambskin roller, brush

#### ■ TDS Consumption

7-10 m<sup>2</sup>/lt (for single coat).

#### ■ Attention points

- Not applicable on wet and damp substrates.

All tools should be cleaned with water after the application before drying.

#### ■ Technical specifications

Product Name	weberprim C 70
Product Type	liquid (density 1,54 gr/cm <sup>3</sup> )
Finishes/Colors	5 colors

#### ■ Storage

Packaging	Net 7,5 lt and 15 lt buckets.
Shelf life	1 year as of the production date in dry and moisturefree environment provided that packages will not be opened. Package should be kept tightly closed when not in use. Package should be protected against frost.

#### ■ Safety Warning

Use the appropriate safety equipment (dust mask, gloves).Protect your Eyes / face.Avoid contact with eyes and skin.In case of contact with eyes, rinse immediately with plenty of water and consult a specialist.Read the Material Safety Data Sheet for more detailed safety information.

#### DISCLAIMER

Since there are different conditions and requirements that apply in any case, Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş. can not be liable for other than the information provided in this product datasheet. The information provided in this product data sheet is based on our current knowledge and experience about the product. All of the above information must be considered as guidelines. It is the user's responsibility to ensure that the product is suitable for the intended use, and also to perform acceptance check and self-inspection control. The user is responsible if the product is used for purposes other than recommended or for improper installation.

The stated times apply for 20 °C substrate and ambient temperature and increase at lower temperatures and decrease at high temperatures. Saint-Gobain Weber Yapı Kim. San. ve Tic. A.Ş. is not responsible for the application errors arising from use of product beyond its intended purpose or failure to comply with the foregoing application conditions and advice on the product.

Saint-Gobain Weber Yapı Kimyasalları San. ve Tic. A.Ş.  
Kemalpaşa OSB Mah. Kuyucak Yolu Sokak No:284 • 35730 Kemalpaşa • İzmir • Türkiye  
Tel: +90 (232) 397 07 00 • www.tr.weber • info@weber.com.tr • Çözüm Hattı 444 6 990

  
SAINT-GOBAIN